

Thermo Cell Transporter 3018

Quality – Made in Germany



Features:

- Factory-aligned temperature at 37 °C
- Different temperature possible (to be advised before order)
- Continuous operation with power supply, car voltage or integrated accumulator during transport
- Operation with batteries up to 5 h*
- Compact design
- * at 22 °C ambient temperature

Transport incubator for safe and versatile use

Technical data:

- Dimensions: 111 x 111 x 215 (w x d x h in mm)
- Weight: 2.4 kg
- Power supply: 100 240 V AC, 50/60 Hz
- Temperature: between 32 °C and 42 °C available (to be advised before order)
- Accuracy of regulation: ± 0.3 °C
- Operation time:
 - with power supply or 12V car voltage continuously
 - with accumulator approx. 5 h*
- Heating up time 22 °C to 37 °C: approx. 1 h*
- Charging time of accumulator: approx. 3 h
- For use with 8 x 13 ml Falcon tubes (REF 13881) or 2 x 13 ml and 8 x 5 ml Falcon tubes (REF 16518)

Scope of supply:

- Basic unit
- Power supply unit
- Car connection cable

REF

13881

for 8 x 13 ml Falcon tubes

16518

for 2 x 13 ml and 8 x 5 ml Falcon

tubes



CE

Rev. 4_08/2017