

## LABOR 140 ECT-F



### Characteristics

<b>Temperature Range</b>	+2 / +15 °C
<b>Capacity</b>	128 lt (4,53 cu ft) <i>Gross capacity 153 lt (5,40 cu ft)</i>
<b>External Dimensions (W x D x H)</b>	cm 52 x 63,5 x 83,5 <i>Internal Dimensions (W x D x H) cm 44 x 51,6 x 56; Weight kg 49</i>
<b>Structure and Insulation</b>	sanitized pre-coated steel with bacteriostatic activity, white colour-in/out (rust- corrosion-proof material), or stainless steel 18/10 AISI 304 inside and sanitized pre-coated steel white colour- outside; insulation polyurethane thickness 40 mm
<b>Feet</b>	n.4 stabilizing feet
<b>Door</b>	Nr 1 blind door pre-coated steel white colour, with ergonomic handle in aluminum
<b>Light</b>	Led type
<b>Suggested internal fittings</b>	nr.2 shelves  <i>Interchangeable system that allows to mix:</i> <ul style="list-style-type: none"> <li>• open wire shelves supported by plastic clips, adjustable in height (dim.cm.50 x 40);</li> <li>• extractible aluminum drawers mounted on telescopic slides (dim. cm.10 x 45 x 7,5 for 3 compartments)</li> </ul>
<b>Controller</b>	ECT-F  <i>ECT-F CONTROL with LCD Display with no.4 soft touch pads, with a 0,1 °C resolution. Customizable menu, available in 5 languages. Acoustic and visual signals for:</i> <ul style="list-style-type: none"> <li>• Open door</li> <li>• High Temperature</li> <li>• Low temperature</li> <li>• Power failure (when the energy returns, only in event of High Temperature)</li> <li>• Dirty Condenser The last 12 events are always available from the display. Clear and precise information of the status of the machine are indicated on the display, as well as all the failures. A password, if enabled, identifies two distinct levels of access to the controller (User and Service), and protects the modification of functional parameters, such as switch on, switch off and set-point of the equipment. The display can be customized, enabling you instant verification of all the main settings for a quick resolution of any problems (Doctor View). Special functions Stop-On-Door, Second Cooling and Advanced Defrosting allow the complete management of the refrigeration cycle, reducing temperature peaks and consumption.</li> </ul>
<b>Alarms</b>	Acustico-visivi per temperature e guasti
<b>Data and Event recording</b>	last 12 events availables from display
<b>Refrigeration Type</b>	Forced-air, ventilated
<b>Defrost</b>	Automatic with automatic evaporation of the condensate water

### Technical data

<b>Details</b>	<ul style="list-style-type: none"> <li>• Refrigerant gas type: R134A CFC free</li> <li>• Mains Voltage 230V/1/50Hz</li> <li>• Power consumption 24H: 2,2 kW/24H</li> <li>• Instant power consumption: 0,11 kW (0,9 A)</li> <li>• Noise level &lt; 42,3 dBA</li> <li>• Ambient Temperature: +16/+38 °C; humidity 60%</li> <li>• Connector: Schuko</li> </ul>
<b>In accordance with</b>	2006/42/CE, 2014/30/CE, 2014/35/CE, 2011/65/CE (RoHS), 2012/19/CE (RAEE) and following modifications
<b>Package</b>	Strong Cardboard on wooden pallet

Dim. cm.55x69x102; Kg.57

- *Wooden crate on wooden pallet available: dim.cm.60x79x105; Kg.76*

## Accessories

---

### Key Lock

#### ECT-F PLUS CONTROLLER

- *- Backup batteries for power alarm up to 48Hrs (24 for 2T)*
- *- Memory of Min and Max temperature reached, resettable by user*
- *- High temperature alarm due to power failure alarm*
- *- Temperature displayed during power failure*
- *- Free contact on the electronic board*
- *- Additional output relays*

### Glass Door

### Rollers

### Castors with brakes

### Additional Shelf

### Extractible Aluminum Drawer with partitions

### Plexiglas front for drawers

### Wire basket in stainless steel H mm 148

### Dry Contact

#### DMLP DIGITAL MONITOR

- *Monitor/alarm/recording system with rechargeable battery, completely independent from the ECT-F controller. The DMLP Digital Monitor works with NTC probes, with 0.1 °C resolution, accuracy +/- 0.3 °C and an LCD 16-letter screen, customizable in 5 languages. With only one accessory you have the following functions:*
- *Temperatures and alarms recorder on removable Secure Digital (SD Back-Up memory): it can store 5 years data, recording temperature and alarms every minute. The SD card can be connected to any PC: a software (Capture) is included, so that you can download, save and print all data from your PC, with fully customizable graphs or tables.*
- *Battery backup: ensures alarms and recording of temperatures even in case of power failure. The battery system lasts about 12 hours.*
- *Dry contact for remote connection + RS485 port*

#### DMLP PRINTER

### Internal Sockets (n.2 with On/OFF)

### Cable port mm 15

### Humidity Sensor

### PT100 probe (free contacts)

### Voltage stabilizer

### 60 Hz Frequency

### 115 V

### Wooden crate Package

---

#### **C.F. di Ciro Fiocchetti & C. s.n.c.**

Via Panagulis, 48 - 42045 Luzzara (RE) Italy  
Tel. +39 0522 976232- Fax +39 0522 976028  
info@fiocchetti.it - www.Fiocchetti.it  
P.I.00934960352  
Registro A.E.E. IT8020000002833