

MEDIKA 400 ECT-F TOUCH



Characteristics

Temperature Range	+2 / +15 °C
Capacity	347 lt (12,26 cu ft) <i>Gross capacity 347 lt (12,26 cu ft)</i>
External Dimensions (W x D x H)	cm 60 x 65,5 x 195,5 <i>Internal Dimensions (W x D x H) cm 50 x 49,3 x 140,5; Weight kg 113</i>
Structure and Insulation	sanitized pre-coated steel with bacteriostatic activity, white colour-in/out (rust- corrosion-proof material), or stainless steel 18/10 AISI 304 inside and sanitized pre-coated steel white colour- outside; insulation polyurethane thickness 70 mm in the back, 50 in the sides
Door	Nr 1 glass door with triple glass panels
Rollers	rollers
Light	Led type with adjustable brightness
Suggested internal fittings	nr.4 shelves <i>Interchangeable system that allows to mix:</i> <ul style="list-style-type: none"> • open wire shelves supported by plastic clips, adjustable in height (dim.cm.47,5 x 46); • extractible aluminum drawers mounted on telescopic slides (dim. cm.12 x 40 x 7,5 for 3 compartments); • stainless steel wired drawer/shelf on telescopic guides (H 6,2 cm)
Controller	ECT-F TOUCH <i>ECT-F TOUCH CONTROLLER with recording and alarms system</i> <i>New controller with TFT 7" touch screen display easily readable from the distance, with a real time graphic of temperatures and of other selected functions always visible from the home page.</i> <ul style="list-style-type: none"> • Temperature recording of the last 10 years • Acoustic and visual alarm system for temperature deviations, open door, condenser, and faulty conditions • Safety thermostat against freezing and overheating • SD card with frontal access: it can store 10 years data recording and relevant documents such as manuals, list of spare parts, videos regarding installation and most common operations. • USB port that allows to download data directly from the front panel • Multimedia section with Tutorial area for instruction movies, service manuals, electrical drawings, etc, • Dry contact for remote connection • RS485 and RJ45 port for LAN/Ethernet. • Password for the turning on and off of the machine, to protect from unauthorized users • Slot for SIM card • Integrated Web Server
Alarms	Acoustic and Visual for temperature deviations and failures, with automatic recording
Safety Thermostat	
Data and Event recording	10 years on SD card; last year on Flash-memory
Temperature Graph	A customizable real time graphic always visible from the home page.
Connectivity	USB-SD-SIM port with frontal access ; Dry Contact; Serial ports RS485 and RJ45
Refrigeration Type	Forced-air, ventilated
Defrost	Automatic with automatic evaporation of the condensate water

Technical data

Details

- Refrigerant gas type: R404A CFC free
- Mains Voltage 230V/1/50Hz

- Power consumption 24H: 1,8 kW/24H
- Instant power consumption: 0,2 kW (1,2 A)
- Noise level < 46 dB
- Ambient Temperature: +16/+38 °C; humidity 60%
- Connector: Schuko

In accordance with	2006/42/CE, 2014/30/CE, 2014/35/CE, 2011/65/CE (RoHS), 2012/19/CE (RAEE) and following modifications
Package	Strong Cardboard on wooden pallet <i>Dim. cm.66x71x212; Kg.127</i> • <i>Wooden crate on wooden pallet available: dim. cm.77x77x213; Kg.150</i>

Accessories

Electric Digital Key Lock

The door is opened by means of a gentle pressure on the key icon in the homepage, and can be password protected. Mechanical key supplied in the event of failure.

Blind Door

Additional Shelf

Extractible Aluminum Drawer with partitions

Plexiglas front for drawers

Sliding wire stainless steel drawer H mm 62

Stainless steel wire rack cm 14 x42 x 15 H (max 3 each shelf)

Drawer for narcotics with keylock H mm 100

Back-up Batteries

nr.8 Nihm rechargeable batteries type AA of 1.2 Volt, easily replaceable, for power failure alarm

External Terminal Board for RS485/Ethernet/Dry Contact

Dmlp Digital Monitor Touch

Independent visual/acoustic alarm and recording system, with an accuracy of 0.1°C thanks to the PT100 probe used for temperature detection. The DMLP will take over alarms functions when installed as integrated module on the main ECT-F Touch controller. It is fed by standard rechargeable batteries to record temperatures and events in case of power failure (Kit Battery Back-up is included). The data downloading is managed by the software CAPTURE supplied into the SD CARD: thanks to this software, it is possible to produce graphics and tabs of recorded data.

DIN 58345 conformity

Includes Electric Digital Key Lock, Back-up batteries for power failure and external terminal board for dry contact

Internal Socket

Internal Sockets (n.2 with On/OFF)

Cable port mm 35 with cap

Cable port mm 15

Humidity Sensor

PT100 probe (free contacts)

Voltage stabilizer

4-20mA converter module

external terminal board included (this accessory excludes the Gsm module)

60 Hz Frequency

115 V

Wooden crate Package

C.F. di Ciro Fiocchetti & C. s.n.c.

Via Panagulis, 48 - 42045 Luzzara (RE) Italy
Tel. +39 0522 976232- Fax +39 0522 976028
info@fiocchetti.it - www.fiocchetti.it
P.I.00934960352
Registro A.E.E. IT8020000002833